

**Manual sealless steel strapping tool for high tension**

---

**Characteristics**

---

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm <sup>2</sup> / 160'000 psi
Strapping dimensions:	widths 12.7 – 19.0 mm / ½ – ¾"
thicknesses	0.50 – 0.70 mm / .020 – .028"
Weights:	5.7 kg / 12.6 lbs Normal-version
	5.9 kg / 13.0 lbs TW-version
Average seal strength:	approx. 80 %
TW-version available:	Torque wrench tensioning system
Suspension (Optional):	Suspension for vertical and horizontal applications; has to be ordered separately
	Handle for horizontal applications; has to be ordered separately

**Advantages**

---

- The special tensioning gear-system allows a high strap tension of up to 5500 N (1240 lbs) with a limited amount of tensioning effort of only 240 N (54 lbs)
- Handy sealless combination tool to strap flat packages (e.g. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals

**Chart of types model A338**

Item No.	Model	Width		Uniflex		Ultraflex	
		mm	inch	Thicknesses		Thicknesses	
				mm	inch	mm	Inch
13.2910	A338/12.7/0.50-0.64	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2915	A338/12.7/0.70/UNI	12.7	1/2"	0.70	.028	-	-
13.2920	A338/13/0.50-0.64	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2925	A338/13/0.70/UNI	13		0.70	.028	-	-
13.2930	A338/16/0.50-0.64	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2935	A338/16/0.70/UNI	16	5/8"	0.70	.028	-	-
13.2940	A338/19/0.50-0.64	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2945	A338/19/0.70/UNI	19	3/4"	0.70	.028	-	-

Uniflex = Regular duty strapping max. 850 N/mm<sup>2</sup> / 123'000 psi

Ultraflex = High tensile strapping max. 1100 N/mm<sup>2</sup> / 160'000 psi

**Chart of types model A338 with torque wrench tensioning system**

Item No.	Model	Width		Uniflex		Ultraflex	
		mm	inch	Thicknesses		Thicknesses	
				mm	inch	mm	Inch
13.2911	A338/12.7/0.50-0.64/TW	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2916	A338/12.7/0.70/UNI/TW	12.7	1/2"	0.70	.028	-	-
13.2921	A338/13/0.50-0.64/TW	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2926	A338/13/0.70/UNI/TW	13		0.70	.028	-	-
13.2931	A338/16/0.50-0.64/TW	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2936	A338/16/0.70/UNI/TW	16	5/8"	0.70	.028	-	-
13.2941	A338/19/0.50-0.64/TW	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2946	A338/19/0.70/UNI/TW	19	3/4"	0.70	.028	-	-

Uniflex = Regular duty strapping max. 850 N/mm<sup>2</sup> / 123'000 psi

Ultraflex = High tensile strapping max. 1100 N/mm<sup>2</sup> / 160'000 psi

TW = Torque wrench tensioning system

**Accessories**

A33.5301 Suspension for vertical and horizontal applications

A33.5307 Handle for horizontal applications