

STRAPPING

MOD. D6RP

Replications





Plastic/Cans



Construction

Glass

06RP Series

The 06RP automatic horizontal strapping machine was designed to apply horizontal straps to palletized products. It comes with a strapping head that works either with polypropylene or polyester straps. It can be placed in full automatic packaging lines, where, by signals exchange can communicate with other machines. It can also operate in stand alone mode. It may also feature a touch-screen operator panel through which to manage all machine functions.

Technical data

Consumption

Power supply	
Voltage	400 V (50Hz)
Installed power	~ 2,0 kW
Air supply	
Pressure	5,5 ÷ 6,5 bar

Coil size	
Max internal diameter	390 ÷ 405 mm
Max external diameter	600 mm

~ 10 NL/cycle

Pack size (standard machine)	
Lenght	1200 mm
Width	800 / 1000 mm

Applicable strapping heads

TR1400 / TR1400HD / TR1800 / TR2000

Strap Type of strap


Polyester (PET) Polypropylene (PP)




Strapping arch detail



Officina Meccanica Sestese S.p.A. 9 Via Borgomanero, 44 - 28040 Paruzzaro (NO) 5 Tel.+39 0322 541411 🖶 Fax +39 0322 53157 🛛 🎽 info@omsspa.com



Standard machine dimensions



06_EN







Corners protection device

www.omsspa.com

As a part of our policy of continuous improvement, we reserve the right to alter design and specifications without prior notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment