

The technologically advanced and versatile wrapping solution



Characteristics

Ring diameters:	50 cm	90 cm	125 cm	160 cm	200/250 cm
Standard film quality:	23 m μ	23 m μ	23 m μ	23 m μ	23 m μ
Film reel dimensions:	100 mm	100, 170, 250 mm	100, 170, 250 mm	100, 170, 250 mm	100, 170, 250 mm
Max. ring speed:	350 rpm	140 rpm	70 rpm	60 rpm	50 rpm
Power supply:	230 V	230/400 V	230/400 V	230/400 V	230/400 V
Power consumption:	0.40 Kw	1.58 Kw	1.61 Kw	1.63 Kw	1.66 Kw
Inverter / PLC:	Fuji / Omron	Fuji / Omron	Fuji / Omron	Fuji / Omron	Fuji / Omron

Advantages

- CE certified
- Proven quality with competitive price
- Easy operation, simple maintenance
- In various inner ring diameters available
- Double film reel dispenser
- Ring protection
- Adjustable stretch film tension
- Automatic film cutter and clamp
- Adjustable ring speed
- Touch screen panel
- Various optional features, i.e.
 - Top press
 - Dispensers

Chart of types model FV350

Item No.	Model	Inner diameter
31.3011	FV350/50	50 cm
31.3012	FV350/90	90 cm
31.3013	FV350/125	125 cm
31.3014	FV350/160	160 cm
31.3015	FV350/200	200 cm
31.3016	FV350/250	250 cm