

Manual sealless steel strapping tool for high tension

**Characteristics**

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi
Strapping dimensions:	widths 12.7 – 19.0 mm / 1/2 – 3/4"
	thicknesses 0.50 – 0.70 mm / .020 – .028"
Weights:	5.7 kg / 12.6 lbs Normal-version
	5.9 kg / 13.0 lbs TW-version
Average seal strength:	approx. 80 %
Versions available:	Torque wrench tensioning system
	MicroLock™ system
Suspension (Optional):	Suspension for vertical and horizontal applications; has to be ordered separately
	Handle for horizontal applications; has to be ordered separately

Advantages

- The special tensioning gear-system allows a high strap tension of up to 5500 N (1240 lbs) with a limited amount of tensioning effort of only 240 N (54 lbs)
- Handy sealless combination tool to strap flat packages (e.g. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals
- The MicroLock™ sealless system guarantees a maximum of security of the sealless steel strapping joint against unlocking

Chart of types model A338

Item No.	Model	Width		Uniflex Thicknesses		Ultraflex Thicknesses	
		mm	inch	mm	inch	mm	inch
13.2910	A338/12.7/0.50-0.64	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2911	A338/12.7/0.50-0.64/TW	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2915	A338/12.7/0.70/UNI	12.7	1/2"	0.70	.028	-	-
13.2916	A338/12.7/0.70/UNI/TW	12.7	1/2"	0.70	.028	-	-
13.2920	A338/13/0.50-0.64	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2921	A338/13/0.50-0.64/TW	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2925	A338/13/0.70/UNI	13		0.70	.028	-	-
13.2926	A338/13/0.70/UNI/TW	13		0.70	.028	-	-
13.2930	A338/16/0.50-0.64	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2931	A338/16/0.50-0.64/TW	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2935	A338/16/0.70/UNI	16	5/8"	0.70	.028	-	-
13.2936	A338/16/0.70/UNI/TW	16	5/8"	0.70	.028	-	-
13.2940	A338/19/0.50-0.64	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2941	A338/19/0.50-0.64/TW	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2945	A338/19/0.70/UNI	19	3/4"	0.70	.028	-	-
13.2946	A338/19/0.70/UNI/TW	19	3/4"	0.70	.028	-	-

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi

Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

TW = Torque wrench tensioning system

Chart of types model A338 with MicroLock™

Item No.	Model	Width		Uniflex Thicknesses		Ultraflex Thicknesses	
		mm	inch	mm	inch	mm	inch
13.2950	A338/12.7/0.50-0.64/ML	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2951	A338/12.7/0.50-0.64/ML /TW	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2955	A338/12.7/0.70/UNI/ML	12.7	1/2"	0.70	.028	-	-
13.2956	A338/12.7/0.70/UNI/ML /TW	12.7	1/2"	0.70	.028	-	-
13.2960	A338/13/0.50-0.64/ML	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2961	A338/13/0.50-0.64/ML /TW	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2965	A338/13/0.70/UNI/ML	13		0.70	.028	-	-
13.2966	A338/13/0.70/UNI/ML /TW	13		0.70	.028	-	-
13.2970	A338/16/0.50-0.64/ML	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2971	A338/16/0.50-0.64/ML /TW	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2975	A338/16/0.70/UNI/ML	16	5/8"	0.70	.028	-	-
13.2976	A338/16/0.70/UNI/ML /TW	16	5/8"	0.70	.028	-	-
13.2980	A338/19/0.50-0.64/ML	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2981	A338/19/0.50-0.64/ML /TW	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2985	A338/19/0.70/UNI/ML	19	3/4"	0.70	.028	-	-
13.2986	A338/19/0.70/UNI/ML /TW	19	3/4"	0.70	.028	-	-

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi

Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

TW = Torque wrench tensioning system

ML= MicroLock™

Accessories

A33.5301 Suspension for vertical and horizontal applications

A33.5307 Handle for horizontal applications