



5 MAST LENGTHS
WRAPPING HEIGHTS
500 - 3.500 MM

MOTION
FLASHING LIGHT &
AUDIO SIGNAL

5 FILM CARRIAGES
3 FILM DIMENSIONS

11" (28 CM)
STATE-OF-THE-ART
(OP1) 6 OR
(OP2) 99 PROGRAMS

MANUAL
MACHINE RELOCATION

FORK LIFT
PICK UP POINTS

HD SAFETY
BUMPER

MAINTENANCE FREE
BATTERIES
OF YOUR CHOICE

FR300 SERIES

With the **NEW FR300 Series Self Propelling Robot** stretch wrapping machines, **FROMM** offers the market a flexible all-rounder with an extensive package of options and sophistication. For example, it can be fitted with a geo-magnetic compass with which, for outsized products, the start and stop position accurately fall on the same point. Other notable options include a film consumption indicator, a film cutting unit, a roping program and a variety of maintenance-free batteries.

First class components

Like all other FROMM wrapping machines, the FR-series is equipped with components and parts available on the market, including inverters, so that availability is large and competitive.

Modular construction

The modular structure makes it possible to even make adjustments after some time.

Ergonomics and operation

When designing the New FROMM FR300 Series Robot wrapping machines, in line with the FROMM vision, great attention was paid to ease of use and safety for multiple operators and the environment. In addition, special attention has been paid to a clear easy to operate, state-of-the-art, 11" (28 cm) Operating Panel. OP1 6 or OP2 with 99 programs

All kinds of packages, in all kinds of places

The FR300 Series are reliable partners for every user and can fully and reliably wrap a wide variety of products and sizes at almost any location.

Adding value to each wrapped package.

Think of regular pallets, glass racks, large and irregular (wood) packages, bundles of bales, bags, construction materials, machines, etc. In addition, Robot wrapping machines are ideally suited for circumstances where wrapping has to be done at different locations.

Multiple efficiency options

In addition to a choice of no less than 5 different mast heights, 5 different film carriages, various batteries and charging stations, options such as a low temperature version (-5°C / 23°F), special film wrapping programs, processing of different film rolls, film cutting unit, special photocells, film consumption meter, wrapping cycle counter, special rubber "non-marking" wheels and different guide wheels to pack size/type, can be added according to your needs.

Contact your FROMM representative for more information and refer to the Data Sheet for a detailed view of the FR300 Series Wrapping Robot.



Your FROMM Distributor